

序号 item	产品代码 part no.	轮辋型号 rim size	重量 (kg) weight	轮辐板厚 disc thickness	风孔数 hand hole no.	风孔形式 hand hole	螺孔数 nut no.	螺孔直径 nut dia.	螺孔形式 nut type	分布圆直 径P. C. D	中孔直径 C. B. D	载荷 (kg) Load	偏距 Offset
1	A165580	16×5.5J	10	16	6	φ 40	6	26	ISO	φ 225	164	1320	103/119
2	A1655B1	16×5.5K	9	14.5	6	80x40椭圆 /Oval	6	24.5	ISO	φ 222.25	164	1320	104/118.5
3	A176050	17.5×6.00	14.2	20	10	φ 32	10	26.75	ISO	φ 225	176	1750	115/135
4	A176060	17.5×6.00	11.7	17	6	φ 32	6	21	ISO	φ 205	160.3	1750	110/127
5	A176062	17.5×6.00	12.9	17	6	φ 40	6	21	ISO	φ 205	161	1815	109/1276
6	A176063	17.5×6.00	13.1	17	6	φ 32	6	32.5	ISO	φ 222.25	161	4000lbs	109/128
7	A176090	17.5×6.00	14.2	20	10	φ 32	10	32.5	ISO	φ 222.25	164	2500	115/135
8	A176093	17.5×6.00	13.6	20	6	φ 50	6	32.5	SR22	φ 222.25	164	1750	115/135
9	A176740	17.5×6.00	12.2	21	8	φ 32	8	24.5	ISO	φ 275	221.1	2500	120/141
10	A176750	17.5×6.75	14.7	21	10	φ 32	10	26.75	ISO	φ 225	176	2500	120/141
11	A176790	17.5×6.75	14.8	21	6	φ 50	6	32.5	SR22	φ 222.25	164	2500	120/141
12	A1767N1	17.5×6.75	12.6	21	8	φ 40	8	17.4	ISO	φ 165.1	121	2745	0/21
13	A197540	19.5×7.50	18.34	22	8	φ 40	8	24.5	ISO	φ 275	221.1	3000	134/156
14	A1975K0	19.5×7.50	18.7	22	8	φ 40	8	32.5	ISO	φ 275	221.1	3000	134/156
15	A221100	22.5×11.75	23.2	24	10	φ 40	10	26.75	ISO	φ 335	281.2	4510	0/24
16	A221101	22.5×11.75	23.91	24.5	10	φ 32	10	26.75	ISO	φ 335	281.2	4510	120/144.5
17	A221102	22.5×11.75	28.6	26	10	φ 32	10	26.75	ISO	φ 335	281.2	5000	118/144
18	A221103	22.5×11.75	24.6	24	10	φ 40	10	26.75	ISO	φ 335	281.2	5000	0/24

序号 item	产品代码 part no.	轮辋型号 rim size	重量 (kg) weight	轮辐板厚 disc thickness	风孔数 hand hole no.	风孔形式 hand hole	螺孔数 nut no.	螺孔直径 nut dia.	螺孔形式 nut type	分布圆直 径P. C. D	中孔直径 C. B. D	载荷 (kg) Load	偏距 Offset
19	A221120	22.5×11.75	28.7	26	10	φ 32	10	26.75	ISO	φ 285.75	220.1	4510	120/146
20	A221170	22.5×11.75	25.2	24	10	φ 40	10	32.5	ISO	φ 335	281.2	4510	0/24
21	A221171	22.5×11.75	24.2	24.2	10	φ 32	10	32.5	ISO	φ 335	281.2	4510	120/144.5
22	A221172	22.5×11.75	26.8	26	10	φ 32	10	32.5	ISO	φ 335	281.2	5000	118/144
23	A221173	22.5×11.75	24.6	24	10	φ 40	10	32.5	ISO	φ 335	281.2	5000	0/24
24	A221300	22.5×13.00	31.7	30	10	φ 40	10	26	ISO	φ 335	281.2	5200	- 15/15
25	A221400	22.5×14.00	32.9	30	10	φ 40	10	26	ISO	φ 335	281.2	5200	- 15/15
26	A221420	22.5×14.00	33.2	25.4	10	φ 40	10	26	ISO	φ 285.75	220.1	5800	0/25.4
27	A221421	22.5×14.00	33.2	25.4	10	φ 40	10	26	ISO	φ 285.75	220.1	5800	25.4/50.8
28	A228200	22.5×8.25	25.51	24.5	10	φ 60	10	26.5	ISO	φ 335	281.2	3650	142.5/167
29	A228201	22.5×8.25	23.4	24.2	10	φ 50	10	26.5	ISO	φ 335	281.2	3650	144.5/168.7
30	A228202	22.5×8.25	23.1	23	10	φ 60	10	26.75	ISO	φ 335	281.2	3650	142.5/165.5
31	A228203	22.5×8.25	21.7	22	10	φ 60	10	26.75	ISO	φ 335	281.2	3650	143/165
32	A228210	22.5×8.25	22.4	24.5	10	φ 60	10	32.5	SR22	φ 285.75	222	3650	144/168.5
33	A228211	22.5×8.25	22.8	24.5	10	φ 60	10	30	SR22	φ 285.75	221.1	3650	144/168.5
34	A228220	22.5×8.25	23.4	24.5	10	φ 60	10	26.75	ISO	φ 285.75	220.1	3650	144/168.5
35	A228223	22.5×8.25	22.7	24.5	7	95×60梯形 /trapezoid	10	26.75	ISO	φ 285.75	220.1	3650	144/168.5
36	A228224	22.5×8.25	24.7	25	10	φ 60	10	26	ISO	φ 285.75	220.1	3650	144/169

序号 item	产品代码 part no.	轮辋型号 rim size	重量 (kg) weight	轮辐板厚 disc thickness	风孔数 hand hole no.	风孔形式 hand hole	螺孔数 nut no.	螺孔直径 nut dia.	螺孔形式 nut type	分布圆直 径P. C. D	中孔直径 C. B. D	载荷 (kg) Load	偏距 Offset
37	A228225	22.5×8.25	22.13	25.5	10	95×60梯形 /trapezoid	10	26.75	ISO	φ 285.75	220.1	3650	144/169.5
38	A228226	22.5×8.25	23.1	24.5	6	99x50椭圆 /oval	10	26.75	ISO	φ 285.75	220.1	3650	144/168.5
39	A228227	22.5×8.25	21.6	22	10	φ 60	10	30	SR22	φ 285.75	221.1	3650	146.5/168.5
40	A228229	22.5×8.25	25.3	25	10	78x56梯形 /trapezoid	10	26.75	ISO	φ 285.75	220.1	3650	144/169
41	A22822A	22.5×8.25	20.5	20.5	10	φ 60	10	26	ISO	φ 285.75	220.1	3650	148/168.5
42	A228230	22.5×8.25	25.42	24.5	8	φ 60	8	32.5	ISO	φ 285	222	3650	142.5/167
43	A228240	22.5×8.25	22.8	24.5	8	φ 60	8	24.5	ISO	φ 285.75	220.1	3650	144/168.5
44	A228241	22.5×8.25	22.8	24.5	8	φ 60	8	26	ISO	φ 275	221.1	3650	144/168.5
45	A228270	22.5×8.25	25	24.5	10	φ 60	10	32.5	ISO	φ 335	281.2	3650	142.5/167
46	A228271	22.5×8.25	23.16	24.2	10	φ 50	10	32.5	ISO	φ 335	281.2	3650	144.5/168.7
47	A228272	22.5×8.25	23.1	23	10	φ 60	10	26.75	ISO	φ 335	281.2	3650	144/167
48	A229000	22.5×9.00	25.8	24.5	10	φ 60	10	26.75	ISO	φ 335	281.2	4125	152/176.5
49	A229001	22.5×9.00	26.9	24.5	10	φ 60	10	26.75	ISO	φ 335	281.2	4125	153.5/178
50	A229002	22.5×9.00	24.8	24.5	10	φ 60	10	26.75	ISO	φ 335	281.2	4125	152/176.5
51	A229003	22.5×9.00	23.8	24	10	φ 60	10	26.75	ISO	φ 335	281.2	4125	152.5/176.5
52	A229004	22.5×9.00	25.7	27	10	φ 32.5	10	26.75	ISO	φ 335	281.2	4125	79/106
53	A229005	22.5×9.00	24.9	24	10	φ 60	10	26.75	ISO	φ 335	281.2	4125	151.5/175.5
54	A229006	22.5×9.00	23.5	23	10	φ 60	10	26.75	ISO	φ 335	281.2	4125	153.5/176.5

序号 item	产品代码 part no.	轮辋型号 rim size	重量 (kg) weight	轮辐板厚 disc thickness	风孔数 hand hole no.	风孔形式 hand hole	螺孔数 nut no.	螺孔直径 nut dia.	螺孔形式 nut type	分布圆直 径P. C. D	中孔直径 C. B. D	载荷 (kg) Load	偏距 Offset
55	A229020	22.5×9.00	25.7	27	10	φ 35	10	26.75	ISO	φ 285.75	220.1	4125	79/106
56	A229021	22.5×8.25	26	24.5	10	φ 60	10	26.75	ISO	φ 285.75	220.1	4535	152/176.5
57	A229023	22.5×9.00	25.7	27	10	φ 35	10	26.75	ISO	φ 285.75	221.1	4125	79/106
58	A229024	22.5×9.00	26.6	24.5	10	φ 60	10	26.75	ISO	φ 285.75	220.1	10000LBS	152/176.5
59	A229070	22.5×9.00	25.24	24.5	10	φ 60	10	32.5	ISO	φ 335	281.2	4125	152/176.5
60	A229071	22.5×9.00	25	24.5	10	φ 60	10	32.5	ISO	φ 335	281.2	4125	152/176.5
61	A229072	22.5×9.00	26.8	25	10	φ 60	10	32.5	ISO	φ 335	281.2	4125	151.5/176.5
62	A2290P0	22.5×9.00	25.6	27	10	φ 35	10	30.5	SR22	φ 285.75	221.1	4510	79/106
63	A2290P1	22.5×8.25	26	24.5	10	φ 60	10	30.5	SR22	φ 285.75	220.1	4535	152/176.5
64	A248210	24.5×8.25	27.6	24	10	φ 60	10	30	SR22	φ 285.75	221.1	3650	145/169
65	A248211	24.5×8.25	27.6	24	10	φ 60	10	30	SR22.225	φ 285.75	221.1	3650	145/169
66	A248221	24.5×8.25	26	21	10	φ 60	10	26.75	ISO	φ 285.75	220.1	3650	148/169
67	A248223	24.5×8.25	26.7	21	7	70.8×105梯形 /trapezoid	10	26.75	ISO	φ 285.75	220.1	3650	148/169
68	A248227	24.5×8.25	25.3	23	10	φ 80	10	26.75	ISO	φ 285.75	220.1	3650	145/169